



FENCEMATE® WINDSCREEN

— WARRANTY —

MANUFACTURING DEFECTS

Windscreen products are warranted completely against manufacturing defects. Such defects include, but are not limited to, uncoated or improperly coated fabric, improper stitching, faulty or improperly placed grommets, defective heat-sealing, or incorrect size. Manufacturing defects would be apparent before use or shortly after cover is put in use and must be delineated to manufacturer at that time. Digital pictures showing defect are required. Manufacturing defect claims for windscreens with extended use may be denied.

Upon verification of defect, manufacturer will either replace cover, repair to customer's satisfaction, or issue full or partial credit.

Manufacturer reserves the right to make the final judgment on the stated options.

Warranty applies under conditions of normal use, but does not apply to problems resulting from unreasonable use, poor installation, mishandling, negligence, improper installation or intentional damage. See installation instructions at coversports.com/windscreen-installation.

WARRANTY IS PRORATED	
Product Code	Warranty
VCM18x14 Classic Mesh	3 years
VCP18X18 ArmorMesh	5 years
PP85	4 years
PP100	4 years
GM90	4 years
VCP1800	4 years

ULTRA-VIOLET LIGHT BREAKDOWN

Windscreens are warranted against fabric breakdown from the ultra-violet (UV) sunlight. UV breakdown is evident through brittleness of fabric, greatly reduced tear strength, and, at times, delamination of coating from base fabric.

Upon verification of defect, covers will be repaired, replaced or credit issued for prorated value of windscreens. Manufacturer reserves the right to make final judgment on the stated options.

Freight charges for replacement of cover are not included under warranty.

WIND DAMAGE

Damage to windscreen resulting from ties breaking and windscreen pulling free from fence is not covered under warranty. It is the responsibility of the installer to attach windscreen panels so they will not break away from the fence during windy periods. Refer to installation guide for more information. Grommets are placed at 18" intervals on windscreen panels and it is strongly recommended that a standard wrap (50 lb. tensile strength) tie or cord be attached through every grommet to minimize wind damage. Refer to Windscreen Installation Instructions provided with every windscreen order. additional copies of the Windscreen Installation Instruction can be provided by calling 800-445-6680 or emailing us at sales@coversports.com.

On privacy screen fabric with woven eyelets, ties should be placed at 18" intervals (or closer). Windscreens higher than 6' must have a lacing lip of grommets or a pipe hem at intervals of 6' or less, otherwise warranty is voided.

Report windscreen defects to sales@coversports.com. Please include proof of purchase.